

TECHNICAL SPECIFICATION – JACOB TWIST

CONSTRUCTION	Tufted Twist	 <p>Axminster Carpets Ltd Axminster, Devon, EX13 5PQ 09</p> <p>EN 14041 Jacob Twist Tufted Carpet 80% Wool/10% Nylon, 10% Polyester</p> <p>Reaction to fire Class C_{ii} - S1 (see EN 14041, Table 3)</p> <p>Slipperiness NPD</p> <p>Formaldehyde E1</p>
PILE YARN	80% Wool/10% Nylon/10% Polyester	
PRIMARY BACKING	Polypropylene	
SECONDARY BACKING	Polypropylene	
PILE WEIGHT ± 5%	1695g/m ²	
PILE HEIGHT ± 0.6mm	7.4mm	
TOTAL CARPET WEIGHT ± 10%	2637g/m ²	
TOTAL CARPET THICKNESS ± 1mm	9.6mm	
GAUGE/PITCH	3.2mm	
TUFT DENSITY ± 5%	14.38cm ²	
WIDTH ± 1.25%	4.00m, 5.00m	
FLAMMABILITY	Hot metal nut test (BS4790) indicates a pass. Methanamine Pill Test (BS6307) indicates a pass.	
SUITABILITY	Very Heavy Domestic, Heavy Contract	
COUNTRY OF ORIGIN	United Kingdom	

GENERAL INFORMATION

COLOUR MATCH	Due to batch variations in dyelots, an exact match for colour between different widths, qualities and samples cannot be guaranteed.
SHADING, PILE PRESSURE OR PILE REVERSAL	These are natural characteristics of all cut pile fabrics. This is especially noticeable on plain and tonal shades or open ground designs, and is the result of pressure causing a change in the direction of the pile, giving light and dark patches, accentuated by room lighting. This does not affect the quality or life of the carpet and is not a fault of manufacture. The regular use of an upright cleaner will help to alleviate this effect.
FADING	Photobleaching is caused when the natural yellow pigment which gives wool its creamy colour reacts with ultra-violet light making the wool appear much whiter. Carpets containing large amounts of undyed wool, such as Berbers, are especially susceptible. Although every care is taken to ensure our dyes meet strict requirements, carpets, as with other natural textiles cannot be dyed absolutely fast to light and with the increase in UV rays, carpets will fade when subjected to daylight. Normal wear and light soiling will also give the appearance of fading and both effects are obviously beyond the control of the manufacturer.
FITTING	All carpets should be professionally fitted in accordance with BS5325 using good quality underlay to BS5808
MATCHING	All patterned carpet may require edge trimming to achieve a pattern match.
MAINTENANCE AND CLEANING	Please refer to our aviation carpet care leaflet or www.axminster-carpets.co.uk .
SPECIFICATION AMENDMENTS	The Company is continually striving to improve our products and reserves the right to substitute raw materials as necessary.